



TECHNICAL DATA SHEET

FRONT:

**LTP POWER STRIPPER
INTENSIVE CLEANER**

FOR TRAVERTINE, STONE, SANDSTONE, SLATE, MARBLE, PORCELAIN, GRANITE, TERRACOTTA, QUARRY, BRICK, CONCRETE AND EXTERNAL PAVING.

SUITABLE FOR INTERIOR & EXTERIOR USE

BACK:

LTP Power Stripper

SUITABLE FOR INTERIOR & EXTERIOR USE

A high performance intensive cleaner for stripping and cleaning of vitrified glazed ceramics, travertine, natural stone, sandstone, slate, marble, granite, terracotta, quarry, brick, concrete, external paving, terrazzo and other mineral floors & walls. Helps remove oxidised linseed oil and other mineral oils.

Directions for use:

N.B. To establish whether the tiles are colour fast and to determine optimal dilution for LTP Power Stripper, always test on an inconspicuous area prior to general application.

Surface cleaning: 1:12 in warm water

Deep stripping: 1: 6 in warm water

In extreme cases e.g. removal of linseed oil 1:4 in warm water

Sweep or dry mop floor to remove grit and surface dirt. Mix stripper solution according to required dilution. Working in manageable sized areas, mop on solution to thoroughly wet floor. Let it work for 5 - 10 minutes, keeping floor damp with further solution should it begin to be absorbed. Agitate floor surface using a mildly abrasive pad. If the floor will stand up to it, machine scrub with a stripping pad. Remove resulting dirty residue using clean warm water and absorbent cloths. If you are treating a large area a wet vacuum will prove helpful. Rinse thoroughly and allow to dry completely before applying further treatments. You may need to repeat washing process a couple of times on severely contaminated surfaces.

Coverage:

Surface cleaning: 60m²/litre (mixed 1:12)

Deep stripping: 30m²/litre (mixed 1:6)

In extreme cases: 15m²/litre (mixed 1:4)

Important: Protect plastics, lino, painted and other sensitive surfaces against splashes.

Attention:

Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves and eye protection. If swallowed do not induce vomiting. In case of accident or if you feel unwell, seek medical advice immediately and show label/container. This product should not be used for every day cleaning of floors that are sealed.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

LTP, Tone Industrial Estate, Milverton Road, Wellington, Somerset, TA21 0AN

Tel: 01823-666-213 Fax: 01823-665-685

www.ltp-online.co.uk info@ltp-online.co.uk